



SPECIFICATIONS:

SWITCH: 73-1352T
 3A/24VDC, 4A/120VAC, 0.5A/125VDC, 2A/240VAC
 PVC INSULATED LEAD WIRES
 303 STAINLESS STEEL
 5/8-18 UNF-2A BARREL THREAD
 ATEX EEx d IIC; II2G; IP68 BASED ON WATER-TIGHT ASSEMBLY
 T6, -30°C TO 75°C MINIMUM

NIPPLE:
 316 STAINLESS STEEL
 EEx d IIC T6; II2GD; IP RATING BASED ON WATER-TIGHT ASSEMBLY

TERMINAL BOX:
 EPOXY COATED, DIE CAST ALUMINUM
 (3) 1/2"FNPT CONDUIT ENTRIES
 (6) POINT TERMINAL BLOCK
 EEx d IIC T6; II2GD; IP65

WIRE	FUNCTION	PIN
RED	N/C	1
BLACK	COM	2
BLUE	N/O	3
		4
		5
		6
GREEN	GROUND	GROUND

REV	DATE	ECO	BY

UNLESS OTHERWISE SPECIFIED
 TOLERANCES: .X ±.03, .XX ±.01,
 .XXX ±.005, ANGLES ±1°
 SURFACE FINISH 125 MICROINCHES
 UNIT OF MEASURE
 INCHES [MM]
 DO NOT SCALE THIS DRAWING
 ASME Y14.5

DRAWN: JAPO DATE: 01/04/2009
 APPROVED:
 MATERIAL:
 DIE:
 THIS DRAWING IS UNCONTROLLED WHEN PRINTED

TOPWORX
 Q#4802 ASSEMBLY
 PART NO. 73-1352T4802 REV 2
 SCALE: NONE SIZE: A SHEET: 1 OF 1

NOTICE: Drawing contains confidential & proprietary material and is furnished upon condition that it will not be used in any way detrimental to the interest of TOPWORX INC.